

WHAT IS CLAIMED IS:

1. An insulation-displacement terminal fitting (T), comprising: a base wall (11), first and second opposed side walls (12) projecting from opposite sides of the base wall (11) and defining a wire-receiving space between the side walls (12), each said side wall 12 being provided with at least one V-shaped insulation-displacement portion (15) projecting into the wire-receiving space, at least one lock (17; 18) projecting into the wire-receiving space in a position spaced from the insulation-displacement portions (15), whereby a wire (W) can be inserted into the wire-receiving space sufficiently for cutting a resin coating (Wa) of the wire (W) by projecting ends of the insulation-displacement portions (15) and bringing a core (Wb) of the wire (W) into contact with the projecting ends of the insulation-displacement portions (15), and wherein the lock (17; 18) bites into at least the resin coating (Wa).

2. An insulation-displacement terminal fitting according to claim 1, wherein the lock (17; 18) is formed by cutting and bending a portion of a selected one of the base wall (11) and the side wall (12).

3. An insulation-displacement terminal fitting according to a claim 1, wherein the lock (17) projects substantially at right angles to at least one of the side wall (12) and the bottom wall (11).

4. An insulation-displacement terminal fitting according to claim 1, wherein the lock (18) is inclined obliquely to project in a direction opposite from an acting direction of an external force along the longitudinal direction of the wire (W).

5. An insulation-displacement terminal fitting according to claim 1, wherein the lock (17; 18) projects by a sufficient distance for contacting the core (Wb).

6. An insulation-displacement terminal fitting according to claim 5, wherein the lock (17; 18) and the insulation-displacement portions (15) project substantially equal distances from the respective side walls.

7. An insulation displacement portion according claim 1, wherein the lock (17; 18) is of a single-plate configuration.

8. An insulation displacement portion according to claim 1, wherein the insulation-displacement portions (15) each are formed by two substantially planar portions (16) that extend at an angle from the respective side wall (12).

090931 0600
T08290 TEE6860

Sub 61

9. An insulation-displacement terminal fitting (T), comprising: a base wall (11), first and second opposed side walls (12) projecting from opposite sides of the base wall (11) and defining a wire-receiving space between the side walls (12), each said side wall 12 being provided with at least one V-shaped insulation-displacement portion (15) projecting into the wire-receiving space, each said side wall further having at least one substantially planar lock (17; 18) projecting into the wire-receiving space in a position spaced from the insulation-displacement portions (15), whereby a wire (W) can be inserted into the wire-receiving space sufficiently for cutting a resin coating (Wa) of the wire (W) by projecting ends of the insulation-displacement portions (15) and bringing a core (Wb) of the wire (W) into contact with the projecting ends of the insulation-displacement portions (15), and wherein the locks (17; 18) bite into at least the resin coating (Wa).

10. An insulation-displacement terminal fitting according to claim 9, wherein the locks (18) are aligned substantially normal to the respective side wall (12).

11. An insulation-displacement terminal fitting according to claim 9, wherein the locks (18) are inclined obliquely to project in a direction opposite from an acting direction of an external force along the longitudinal direction of the wire (W).

12. An insulation-displacement terminal fitting according to claim 9, wherein the locks (17; 18) project by a sufficient distance for contacting the core (Wb).

13. An insulation-displacement terminal fitting according to claim 12, wherein the locks (17; 18) and the insulation-displacement portions (15) project substantially equal distances from the respective side walls (12).

al 14. An insulation-displacement terminal fitting according to claim 9, comprising a front end defining an engaging portion (13) for engaging a mating terminal, the insulation displacement-terminal portions (15) being rearward of the engaging portion (13), the locks (17; 18) being rearward of the insulation-displacement portions (15).

09893931 062801